



Constant Temperature Water Bath



SALIENT FEATURES:

- High accuracy PID controller
- Low water cut off helps prevent damage to heater due to low water
- High-grade stainless-steel interior
- High density glass wool insulation
- Sensor detects human presence, auto stops if senses that no one is around to unnecessary usage after working hours

SPECIFICATIONS:

Model	KCWB-2	KCWB-4	KCWB-6
Make	KLABS	KLABS	KLABS
Configuration	1 Row, 2 Hole	2 Row, 4 Hole	2 Row, 6 Hole
Volume	6 Litre	12 Litre	18 Litre
Tank Size (mm)	305 x 160 x 130	305 x 305 x 130	470 x 305 x 130
Temp. Range	RT+5°C to 100°C	RT+5°C to 100°C	RT+5°C to 100°C
Temp. Resolution	0.1°C	0.1°C	0.1°C
Temp. Accuracy	0.5°C	0.5°C	0.5°C
Temp. Control Accuracy	0.5°C	0.5°C	0.5°C
Temp. Control Uniformity	1°C	1°C	1°C
Timing Range	1 min to 99h 59 min		
Tank Material	Stainless Steel 304		
Outer Body Material	Mild Steel with powder coating		
Heater Type	Stainless steel U-type heater		
Temp. Control System	PID	PID	PID
Heating Power	600W	800W	1200W
Safety Features	Low water cut off, Human sensor		
	short-circuit protection		
Power Supply	AC 220V / 50 Hz	AC 220V / 50 Hz	AC 220V / 50 Hz
Dimensions (mm)	380 x 240 x 240 mm	380 x 240 x 240 mm	380 x 240 x 240 mm

Technical Specifications

Model	KCWB-8
Make	KLABS
Configuration	2Row, 8 Hole
Volume	23 Litre
Tank Size (mm)	600 x 300 x 130
Temp. Range	RT+5°C to 100°C
Temp. Resolution	0.1°C
Temp. Accuracy	0.5°C
Temp. Control Accuracy	0.5°C
Temp. Control Uniformity	1°C
Timing Range	1 min to 99h 59 min
Tank Material	Stainless Steel 304
Outer Body Material	Mild Steel with powder coating
Heater Type	Stainless steel U-type heater
Temp. Control System	PID
Heating Power	1500W
Safety Features	Low water cut off, Human sensor short-circuit protection
Power Supply	AC 220V / 50 Hz
Dimensions (mm)	635 x 340 x 210 mm

STANDARD ACCESSORIES:

- Lid
- Heater cover
- Adapter
- Instruction Manual